

STATISTICS OF WORKINGS IN COAL-MINES, 1910—continued.

Name of Mine and Locality.	Name of Manager.	Number of Years worked.	Quality of Coal.	No. of Seams worked.	Thickness of Seams.	Thickness worked.	Dip of Seam.	System of Underground Working.	Number of Shafts.	Dimensions of Shafts.		Output delivered by	Output for 1910.			Approximate Total Output to 31st December, 1909.	Approximate Total Output to 31st December, 1910.	Number of Men ordinarily employed.			Power used for drawing Mineral.	Pumps.		Means of Ventilation.	Date of Inspector's Last Visit.
										Size of Shaft or Adit.	Depth of Shaft or Length of Adit.		Coal.	Slack.	Total.			Above.	Below.	Total.		Stroke.	Size of Barrel.		

SOUTHERN INSPECTION DISTRICT—continued.

CENTRAL OTAGO—continued. Alexandra, Alexandra	Barnes, A. E.	30	lignite	1	14'	7'	1 in 7	bord and pillar	1 1/2' x 2' 6" 6' x 4'	60' 15 ch.	adit	3,373	3,373	75,182	75,182	1	8	9	steam	Snow pump	exhaust steam from pump	..		
Molynex (New Alexandra Coal Company), Alexandra	Pollock, J.	12	"	1	28'	9'	1 in 20	"	2 6' x 4' 5' x 4'	60' 80'	shaft	5,848	1,860	98,497	100,705	4	13	17	"	3-throw ram pump & Snow pump	steam and exhaust from pump engine	..		
Cambrian, Cambrian	McGuckin, J.	26	"	1	9'	all	..	open	open	14,488	14,488	horse		
Welsman's Gully, Cambrian	McGuckin, J. (permit)	49	"	1	30'	"	..	"	"	33,116	33,116	1	..	1	
Laudervale (Jones's), Cambrian	Jones, Robert	6	"	1	..	"	..	"	"	168	266	434	1	..	1
St. Bathian's, St. Bathian's	Enwright, J.	13	"	1	indefinite	15'	..	"	"	222	4,616	5,038	2	..	2
Rough Ridge, Otarehua	Beek, W. (permit)	24	"	1	35'	all	..	"	"	781	25,057	25,838	2	..	2
Idaburn (Waite's), Otarehua	White, J. (permit)	40	"	1	20'	"	..	"	"	775	40,586	41,311	2	..	2
Otarehua, Otarehua	Thomas, K. (permit)	..	"	1	7'	"	..	"	"	336	489	825	1	..	1
Gimmerburn, Gimmerburn	Dougherty, C.	54	"	1	12'	14'	1 in 2	levels	dip incline	48	..	3,013	3,061	1	..	1	hand
Clyde (including Dairy Creek, Clyde)	Turner, G. F.	38	brown	2	40'	"	open	2,159	..	53,764	55,924	1	4	5	steam	steam-driven	natural	
Cardrona, Cardrona	McDougal, R. (permit)	26	"	1	30'	all	vertical	open	open	473	..	23,876	24,349	4	..	4	horse	
Gibbston, Gibbston	Duncan, J.	24	"	1	15' to 40'	..	1 in 3	bord and pillar	..	22 ch.	adit	843	..	16,914	17,757	1	2	3	steam
Shepherd's Creek, Bannockburn	Hodson, J. (Cromwell and Bannockburn, Coleridge Co.; T. K. Harty, managing director)	33	"	1	8'	7'	1 in 4	ditto	1 4' x 3' 6' x 6'	34' 897' 200'	incline	5,233	..	60,426	65,659	4	13	17	..	steam driven	exhaust steam from pump	
Excelsior, Bannockburn	Whittlesstone, A. W.	16	"	1	6'	5'	1 in 4	"	1 1/2' x 5' 6"	20 ch.	adit	59,202	59,202	steam-driven	natural	
Cairnmuir, Bannockburn	Hobson, J.	8	"	1	20'	10'	1 in 1 to 1 in 2	levels & headings	dip incline	3,769	..	17,116	20,885	1	8	9	..	steam-driven	"
Ranfurly, Bannockburn	Toms, R.	vertical	open	654	..	654	5,589	1	3	4
Nevis, Nevis	Toms, R. (permit)	14	brown	1	20'	..	vertical	bord and pillar	adit	946	6,078	1	3	4	hand
Ryder's, Nevis	Toms, R. (permit)	10	"	1	45'	..	vertical	pillar	open	625	7,339	1	..	1
Nevis Crossing, Nevis	Ritchie, Robert (permit)	7	"	1	vertical	open	open	625	..	7,964	7,964	1	..	1