

- (b) If the vehicle is equipped with suitable mechanical signalling-apparatus capable of giving a signal closely corresponding to the signal described in paragraph (a) of this clause, he may indicate his intention by means of the said apparatus.

REGULATION 16.—SPECIAL PROVISIONS RELATING TO
MOTOR-CYCLES.

(1) The following special requirements apply to motor-cycles in addition to those requirements of this Part which apply to motor-vehicles inclusive of motor-cycles.

Head-lamp.

(2) No person shall during hours of darkness operate a motor-cycle unless it is equipped with one head-lamp attached thereto, which shall conform to the requirements of paragraph (c) of clause (2) and paragraph (a) of subclause (i) of clause (4) of Regulation 7 hereof.

Brakes.

(3) No person shall operate a motor-cycle unless it is equipped with at least one brake attached thereto which is capable of bringing to a standstill the motor-cycle and the side-car (if any) attached thereto, without assistance from the compression of the engine, within a distance of 40 ft. from a speed of twenty miles per hour upon a hard, dry, level roadway free of loose material, and which is capable of easy adjustment, and is maintained so that at all times it is efficient and in good working order.

Foot-rests.

(4) No person shall operate any motor-cycle unless adequate foot-rests are attached thereto for the use of every person carried thereon otherwise than in a side-car.

Silencers.

(5) No person shall operate a motor-cycle unless it is equipped with a silencer which is effective and in good working order, and is so constructed or adapted that it is impossible to interfere readily with the effectiveness of the silencer at any time.

Loading.

(6) No person shall operate any motor-cycle (whether with a side-car attached or not) if any part of the vehicle or its load projects more than 2 ft. in front of or more than 3 ft. to the rear of the wheels of such motor-cycle, or projects more than 1 ft. 6 in. on either side of the longitudinal centre-line of the motor-cycle unless a side-car is attached, when the load may project not more than 6 in. beyond that side of the side-car which is farthest from the motor-cycle.